

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A system for testing a performance capability of a user drop in a communication network, the system comprising:
a host terminal coupled to the user drop via the communication network, wherein the host terminal is operable to:
provide a test signal to the user drop, wherein the test signal is a video signal; and
authorize access to the test signal; wherein authorizing access to the test signal is based at least in part upon receiving a network sign-on identifier via the user drop.
2. (Currently Amended) The system of claim 1, wherein ~~the test signal is a video signal~~, the system further ~~comprising~~ comprises:
a network video signal source to generate the video signal.
3. (Currently Amended) The system of claim 1, wherein the test signal ~~[[is]]~~ also comprises a data signal, the system further comprising:
a network data test source to generate the data signal.
4. (Canceled)
5. (Original) The system of claim 1, the system further comprising:
a network entitlement controller arranged to identify a test device coupled to the user drop.

6. (Currently Amended) A method for testing a performance capability of a user drop in a communication network, the method comprising:
- coupling a test device to the user drop, wherein the test device comprises a sign-on identifier that identifies the test device;
 - receiving a test signal at the test device, wherein the test signal is a data test signal that is received at least in part based on the sign-on identifier; and
 - measuring the test signal to determine the performance capability of the user drop.
7. (Currently Amended) A method for implementing performance capability testing of a user drop in a communication network, the method comprising:
- providing access at the user drop to a test signal from a central office, wherein the test signal is a video test signal;
 - receiving a network sign-on identifier at the central office, wherein the network sign-on identifier identifies a test device; and
 - authorizing access to the test signal by the test device.
8. (Canceled)
9. (Currently Amended) The method of claim 7, wherein the test signal ~~is a combination of two or more of the following signal types: a video signal,~~ also comprises a data signal, or a VDSL signal.
10. (Currently Amended) The method of claim 7, wherein ~~at least a portion of the test signal is a video signal,~~ the method further ~~comprising~~ comprises:
- providing a video test source, wherein the video signal is produced by the video test source.

11. (Currently Amended) The method of claim 7, wherein ~~at least a portion of~~ the test signal ~~[[is]]~~ also comprises a data signal, the method further comprising:
providing a data test source, wherein the data signal is produced by the data test source.

12-14. (Canceled)

15. (Currently Amended) A method for testing a performance capability of a user drop in a communication network, the method comprising:
coupling a test device to the user drop, wherein the test device comprises a network sign-on identifier that identifies the test device;
receiving a signal at the test device via the user drop, wherein the signal is a test signal received at least in part based on the sign-on identifier, and wherein the signal comprises a ~~first signal type~~ a video test signal and a second signal type; and
measuring the signal to determine the performance capability of the user drop.

16. (Original) The method of claim 15, the method further comprising:
signing on to the communication network using the network sign-on identifier, wherein signing on provides access to the test signal.

17. (Currently Amended) The method of claim 16, wherein ~~the first signal type and the second signal type~~ ~~[[are]]~~ is selected from the group consisting of a data test signal, ~~a video test signal,~~ and a VDSL test signal.

18. (Currently Amended) The method of claim 15, wherein the ~~[[first]]~~ second signal type is a data test signal and the performance capability is a data performance capability.

19. (Previously Presented) The method of claim 15, wherein the communication network comprises a DSL-based video and data communication network.

20-27. (Canceled)

28. (Previously Presented) The system of claim 2, wherein the video signal comprises a MPEG video signal, and the network video signal source comprises an MPEG2 encoder.

29. (Previously Presented) The system of claim 2, wherein the host terminal comprises a set top box.

30. (Previously Presented) The system of claim 29, wherein the set top box comprises an identifier value that includes the network sign-on identifier.

31. (Previously Presented) The system of claim 30, wherein the identifier value comprises a MAC address.

32. (Previously Presented) The system of claim 1, wherein the host terminal is in communication with a universal system access multiplier on the communication network.

33. (Previously Presented) The system of claim 32, wherein the communication network comprises a fiber-to-the-neighborhood distribution system.

34. (Previously Presented) The system of claim 1, wherein the host terminal is in communication with broadband network unit on the communication network.

35. (Previously Presented) The system of claim 34, wherein the communication network comprises a fiber-to-the-curb distribution system.

36. (Previously Presented) The method of claim 6, wherein the sign-on identifier comprises a MAC address.

37. (Currently Amended) The method of claim 6, wherein the test signal is ~~selected from the group consisting of~~ further comprises a data test signal, a video test signal, ~~and a VDSL test signal.~~

38. (Currently Amended) The method of claim 6, wherein the test signal ~~is a combination of two or more of the following signal types: a video signal, a data signal, or~~ further comprises a VDSL signal.

39. (Previously Presented) The method of claim 6, wherein at least a portion of the test signal is a video signal, the method further comprising:

providing a video test source, wherein the video signal is produced by the video test source.